









Fluo Yellow

COLOUR OPTIONS

















PINNACLE EXO ANSI

MULTI-IMPACT & VOLT RATED HELMET WITH INTEGRATED EPS

ZPE02

The Pinnacle Exo is a multi-impact tested helmet with electrical protection, ideal for all types of electrical work carried out at height, electric & energy industries & busy worksites. Manufactured in Italy, the stylish & versatile design of the helmet enables multiple configurations of head, vision, face and hearing protection. Pinnacle Visors fit directly to the helmet. Integrated Euro slots for hearing protection & face visors assemblies.

Lightweight construction and padded inner lining provide unrivalled comfort, closed-shell provides resistance to risk of electric shock and arc flash. The Exo is also resistant to molten metal splash and lateral deformation.

CERTIFICATION;

ANSI/ISEA Z89.1-2014, Type I, Class E, 20,000 Volts

EN12492:2012,

PR4.2.1 (Shock absorption), PR4.1.3 (Chinstrap Retention System) PR4.2.3.(Chinstrap Retention System Strength <500N)

EN 397:2012+ A1:2012;

LD, MM, -40°C to +50°C. Resistance to lateral deformation (LD); Protection against molten metal splashes (MM); Protection against impacts at low temperatures (-40°C); Protection against impacts at high temperatures (+50°C)

EN50365:2002;

PR 6.3.4, PR 6.3.5 Class 0, 1500 Vdc, 1000 Vac

RATING: to **C**€, -40°C / +50°C ANSI, -18°C / +49°C

LIFESPAN: Up to 10 Years

| MODEL | REF | WEIGHT (G) | SIZE | MATERIAL | APPLICATIONS C € |
|------------|--|---------------|-----------------------------|---|------------------|
| ZPE02 ANSI | Volt rated multi impact helmet with electrical protection ANSI Type 1 Class E | 450g | 54 – 62cm 21.3 – 24.4 in | Exterior Shell ABS plastic, Interior EPS, Fire Resistant Chinstrap | |

PRODUCT FEATURES

- ABS Advanced Thermo Material Shell exterior.
- Non-vented as required for electrical insulation.
- Optional PInnacle Visors and Arc Flash Shields are available in several styles for added eye and face protection.
- 10 year lifespan.
- PPE category: Type 1, Class E
- Inside protection in high-density EPS polystyrene.
- Lightweight and comfortable, just 450gms.
- Dielectric with no metal parts.
- Front & crown paddings absorbs moisture for breathability and are easily removable for washing.

- Attachment loop on chinstrap provided for clipping the helmet to a harness.
- Adjustable fire rated (FR) polyester chinstrap, will not release under force of F>500N.
- Headlamp clips are compatible with all headlights with elastic straps.
- One size fits most including larger heads, with quick wheel up/down adjustable size system, Diameter: 54 - 62cm, 21.3 - 24.4 in.
- Made in Italy.
- Hearing protection kits available on request.
- Integrated Euro attachment system for hearing protection and full hearing/face protection configurations such as forestry.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA Harewood, Christchurch 8053 New Zealand sales.nz@zeroheightsafetv.com

EUROPE & UK Badenerstrasse 122 5466 Kaiserstuhl, Switzerland sales.eu@zeroheightsafety.com

